

# NORAM SX™ Stock Material

*NORAM SX™ is the trademark for the austenitic stainless steel, UNS S32615, which was developed by Sandvik in Sweden specifically for the use in hot concentrated Sulphuric Acid. SX steel is considered the benchmark in sulphuric acid service with over 30 years of unparalleled performance offering numerous advantages over other materials of construction.*

## NORAM SX™ Plate

|       | 2000 x 3000 | 2000 x 6000 | 2300 x 6000 | 2400 x 6000 | 2000 x 8000 |
|-------|-------------|-------------|-------------|-------------|-------------|
| 3 mm  |             | In stock    |             |             |             |
| 4 mm  |             | In stock    | In stock    |             |             |
| 6 mm  |             | In stock    |             | In stock    | On request  |
| 8 mm  |             | In stock    |             |             | On request  |
| 10 mm | In stock    | On request  |             |             |             |
| 15 mm | In stock    | On request  |             |             |             |
| 20 mm | In stock    | On request  |             |             |             |
| 25 mm | In stock    | On request  |             |             |             |
| 30 mm | In stock    | On request  |             |             |             |
| 40 mm | In stock    | On request  |             |             |             |

## NORAM SX™ Welding Material

### TIG Rods, GTAW

|         |           |
|---------|-----------|
| 2.0 mm  | 5 kg/pack |
| 2.4 mm  | 5 kg/pack |
| 3.25 mm | 5 kg/pack |

### MIG Wire, GMAW

|             |            |
|-------------|------------|
| 0.9 mm      | 15 kg/pack |
| 1.14/1.2 mm | 15 kg/pack |
| 1.6 mm      | 15 kg/pack |

### Welding Electrodes, SMAW

|         |             |
|---------|-------------|
| 2.0 mm  | 2.5 kg/pack |
| 2.5 mm  | 2.5 kg/pack |
| 3.25 mm | 3.0 kg/pack |

## NORAM SX™ Mesh

Mesh 1.6 mm – Pitch 4.4 mm

## NORAM SX™ Wire

SX Wire 5.5 mm 500kgs/coil

